MINGOZZI GROUP

www.pirodiserbo.it

SPAZZATRICE

SWEEPER

OFFICINE MINGOZZI

44010 Bando - Ferrara - ITALY

info@pirodiserbo.it

☏ **+39 0532.807106**

MINGOZZI GROUP

www.pirodiserbo.it

SPAZZATRICE

SWEEPER

SPAZZATRICE

RIMUOVE DAL TERRENO I RESIDUI COLTURALI

La macchina è dotata di una spazzola operatrice in nylon a comando idraulico. Questo sistema permettere di raccogliere dalla superficie del terreno il residuo colturale in maniera uniforme anche in presenza di prodotto bagnato o staccato da terra. La macchina è corredata da un rullo posto dietro la spazzola che permette la corretta registrazione della altezza di lavoro dell'attrezzatura. Il ribaltamento del contenitore di raccolta è effettuato tramite due pistoni idraulici che consentono di scaricare il prodotto raccolto su di un piano che ha un'altezza da terra di mt. 1,20.

MINGOZZI GROUP

www.pirodiserbo.it

Il peso contenuto dell'attrezzatura unito alla bassa potenza richiesta alla presa di forza del trattore permette il suo utilizzo anche ad una piccola trattrice.
Nel caso in cui il trattore utilizzato non fosse in grado di sollevare la macchina nelle fasi di manovra questa, tramite apposito attacco, potrebbe essere solamente trainata.
In funzione del prodotto da raccogliere la velocità di lavoro può variare da 2 a 4 km/ora.
L' attrezzatura è costruita in larghezze diverse a seconda delle esigenze colturali.

SWEEPER

REMOVES CROP RESIDUES FROM THE SOIL

The machine is equipped with a hydraulically operated nylon working brush. This system allows the crop residue to be collected uniformly from the soil surface even in the presence of wet or already detached product.
The machine features a roller behind the brush that ensures proper adjustment of the equipment's working height.
The container holding the collected product is overturned with the assistance of two hydraulic pistons, enabling the product to be unloaded onto a floor with a ground clearance of 1.20 meters.
The low weight of the equipment and the low power required for the tractor's PTO allow the use of a small tractor.
If the tractor is unable to lift the machine, it could only be towed using a special attachment.
Depending on the product being collected, the working speed can vary from 2 to 4 km/h.
The equipment is built in different widths depending on the cultivation needs.

MINGOZZI GROUP

www.pirodiserbo.it